

GL Series

Coaxial Monitor

Description

The POPE Professional® GL-12CX is an ultra-compact, high performance coaxial stage monitor which combines maximum enclosure volume with optimum presentation angle in a low profile and contemporary design. It features a high-performance 12" (300 mm) Ferrite Coaxial driver unit mounted on a differential dispersion enclosure.

Features

- 116 dB peak SPL
- 12" Ferrite Coaxial driver
- 2 x 4 pin Speakon® inputs and loop-through
- Lightweight plywood cabinets with tongue and groove joints
- Weather Proof Paint with 16 gauge steel grille

Specifications

Model	: GL-12CX
Class	: 1*12" Coaxial Monitor Speaker
Power Rating	: 450 W Continuous*
Frequency Range	: 60Hz - 20kHz (-10dB)
Frequency Response	: 65Hz - 20kHz (± 3dB)
SPL**	: 110dB Continuous, 116dB peak

Transducer Sections

Low Frequency	: 1*12" (300 mm) Diameter POPE Professional® Transducer
Voice Coil Diameter	: 75 mm (3")
Voice Coil Material	: Copper In/Out
Magnet Material	: Ferrite
Power Rating	: 350 Watts Continuous. Pink Noise 700 Watts Program 1400 Watts Peak
Sensitivity	: 98dB SPL (1W @ 1m)
Nominal Impedance	: 8Ω


High Frequency	: 3" (75 mm) Compression driver
Power Rating	: 100 Watts Continuous. Pink Noise. 200 Watts Program 400 Watts Peak
Voice Coil Diameter	: 75 mm (3")
Magnet Material	: Ferrite
Diaphragm Material	: Titanium
Voice coil Material	: CCAW
Sensitivity	: 107dB SPL (1W @ 1m)
Nominal Impedance	: 8Ω
Crossover Frequency	: 1.8 kHz

Enclosure

Cabinet Construction	: Trapezoidal, 18 mm, 11-ply plywood
Suspension / Mounting	: Floor & 35mm pole mount
Grille	: Powder coated, black, 16-gauge perforated steel grille with charcoal foam backing
Input Connectors	: 4 Pin Speakon (x2) +1-1
Surface Finish	: SoundFlex® environment friendly coating
Coverage Angular	: 55°
Monitor Taper	: 35°
Packing	: Foam with wooden crate carton packing or Flight case - optional
Dimensions (H x W x D)	: 325 mm × 545 mm × 462 mm
Net Weight	: 18 kg
Gross Weight	: 26 kg

Applications

- Speech reinforcement
- Live performance stage monitoring
- Reinforcement of vocal and music



Description

The POPE Professional® GL-15CX is a compact, high performance 15" coaxial stage monitor combining high output and controlled dispersion with discreet, contemporary design. It features a high performance 15" (380 mm) Ferrite Coaxial driver unit mounted on a differential dispersion enclosure. Differential dispersion technology increases the area over which a constant SPL and consistent frequency response is maintained at ear height, enabling the artist to move around the stage more freely.

Features

- 120 dB peak SPL
- 15" Ferrite Coaxial driver
- 2x4 pin Speakon® and loop-through
- Lightweight plywood cabinets with tongue and groove joints
- Weather Proof Paint with 16 gauge steel grille

Specifications

Model	: GL-15CX
Class	: 1*15" Coaxial Monitor Speaker
Power Rating	: 600 W Continuous*
Frequency Range	: 54Hz - 20kHz (-10dB)
Frequency Response	: 60Hz - 20kHz (± 3dB)
SPL**	: 114dB Continuous, 120dB peak

Transducer Section

Low Frequency	: 1*15" (380 mm) Diameter POPE Professional® Transducer
Voice Coil	: 75 mm (3")
Voice Coil Material	: Copper In/Out
Magnet Material	: Ferrite
Power Rating	: 500 Watts Continuous. Pink Noise 1000 Watts Program 2000 Watts Peak
Sensitivity	: 97dB SPL (1W @ 1m)
Nominal Impedance	: 8Ω

High Frequency	: 3" (75 mm) Compression driver
Power Rating	: 100 Watts Continuous. Pink Noise. 200 Watts Program 400 Watts Peak


Voice Coil Diameter	: 75 mm (3")
Magnet Material	: Ferrite
Diaphragm Material	: Titanium
Voice coil Material	: CCAW
Sensitivity	: 107dB SPL (1W @ 1m)
Nominal Impedance	: 8Ω
Crossover Frequency	: 1.8 kHz

Enclosure


Cabinet Construction	: Trapezoidal, 18 mm, 11-ply plywood
Suspension / Mounting	: Floor & 35mm pole mount
Grille	: Powder coated, black, 16-gauge perforated steel grille with charcoal foam backing
Input Connectors	: 4 Pin Speakon (x2) +1-1
Surface Finish	: SoundFlex® environment friendly coating
Coverage Angular	: 55°
Monitor Taper	: 35°
Packing	: Foam with wooden crate carton packing or Flight case - optional
Dimensions (H x W x D)	: 393 mm × 645 mm × 562 mm
Net Weight	: 26 kg
Gross Weight	: 36 kg

Applications

- Speech reinforcement
- Live performance stage monitoring
- Reinforcement of vocal and music



FRONT



SIDE